

Linear Systems and Signals

Signals entering systems

Anand D. Sarwate

Department of Electrical and Computer Engineering
Rutgers, The State University of New Jersey

2020




Learning objectives

The learning objectives for this section are:

- explain how signals enter into systems “flipped”



What is a system?




A system is a function that maps an input signal to an output signal.

- Abstracts away the internal operations: systems are equivalent if they have the same I/O behavior.
- Can characterize different system properties in terms of properties of the I/O behavior.



Systems in a block diagram




We represent systems as boxes in our block diagrams. Some examples:

- Delay: $y(t) = x(t - \tau)$.
- Accumulator: $y[n] = \sum_{k=-\infty}^n x[k]$
- Rectifier: $y(t) = |x(t)|$
- Squaring: $y[n] = |x[n]|^2$.
- Downsampler: $y[n] = x[nN]$



Signals entering a system





Let's look at a signal going into a system. The signal is

$$x[n] = \delta[n] + 2\delta[n-1] \quad (1)$$

At time 0 the sample $x[0]$ should enter the system. But this isn't physically how it looks!




Signals enter... backwards



The trick is that the signal enters the system “backwards” or *flipped*. This is an important concept that will come up when we discuss convolution.

Preview of convolution



Suppose

$$y[n] = 3x[n] + 2x[n - 1] + x[n - 2]. \quad (2)$$

We can see how the input signal enters and leaves the system by sliding the flipped signal into the system.