

Linear Systems and Signals

Block diagram basics

Anand D. Sarwate

Department of Electrical and Computer Engineering
Rutgers, The State University of New Jersey

2020



Learning objectives

The learning objectives for this section are:

- represent basic signal manipulations in terms of block diagrams
- translate a block diagram into a mathematical formula



Block diagrams



In Signals and Systems we look at engineering problems from a “boxes and arrows” perspective:

- arrows are like wires that carry signals
- boxes are systems that transform signals

We can represent these in diagrams that show how signals are being processed and manipulated by systems.



Gain





A *gain* is just scalar multiplication. We call this a gain even if $|\alpha| < 1$ (which is an attenuation).

$$y(t) = \alpha x(t) \quad (1)$$



Addition




An *adder* just sums its inputs:

$$y(t) = x_1(t) + x_2(t) \quad (2)$$



Combining them




We can combine adders and gains:

$$y(t) = \alpha_1 x_1(t) + \alpha_2 x_2(t) \quad (3)$$

$$y[n] = \alpha_1 x_1[n] + \alpha_2 x_2[n] \quad (4)$$



Combining them




We can combine adders and gains:

$$y(t) = \alpha_1 x_1(t) + \alpha_2 x_2(t) \quad (3)$$

$$y[n] = \alpha_1 x_1[n] + \alpha_2 x_2[n] \quad (4)$$

Delay




Delays are also important components of block diagrams.

- Generically we can write a delay of τ as $\text{delay}(\tau)$.



Delay




Delays are also important components of block diagrams.

- Generically we can write a delay of τ as $\text{delay}(\tau)$.
- We will see that $\delta(t - \tau)$ describes a CT system that delays its input by τ .



Delay




Delays are also important components of block diagrams.

- Generically we can write a delay of τ as $\text{delay}(\tau)$.
- We will see that $\delta(t - \tau)$ describes a CT system that delays its input by τ .
- For DT we write a delay of k as z^{-k} (the reason will be clearer later).



Combining them



- delay and gains *commute*. That is, in CT


$$\underbrace{x(t)} \rightarrow \underbrace{3x(t)} \rightarrow \underbrace{3x(t-1)} \leftarrow \underbrace{x(t-1)} \leftarrow \underbrace{x(t)}, \quad (5)$$

and in DT

$$\underbrace{x[n]} \rightarrow \underbrace{-2x[n]} \rightarrow \underbrace{-2x[n-4]} \leftarrow \underbrace{x[n-4]} \leftarrow \underbrace{x[n]}. \quad (6)$$



Systems



A system is a function that maps one signal to another. Here we have


$$y[n] = H_1(x_1[n]) + H_2(x_2[n]) \quad (7)$$

If $H_1(x[n]) = x[n]^2$ and $H_2(x[n]) = 3x[n+1] - 3x[n-1]$ then

$$y[n] = x_1[n]^2 + 2x_2[n+1] - 3x_2[n-1]. \quad (8)$$



Systems



A system is a function that maps one signal to another. Here we have


$$y[n] = H_1(x_1[n]) + H_2(x_2[n]) \quad (7)$$

If $H_1(x[n]) = x[n]^2$ and $H_2(x[n]) = 3x[n+1] - 3x[n-1]$ then

$$y[n] = x_1[n]^2 + 3x_2[n+1] - 3x_2[n-1]. \quad (8)$$



Modulation




One particular system that appears a lot in communication systems is a *modulator*. You modulate a signal $x(t)$ onto a signal $c(t)$ by multiplying the two signals pointwise. Typically $c(t)$ is a high-frequency sinusoid.

$$y(t) = x(t) \cos(2\pi f_c t) \quad (9)$$




Modulation example



If there is some delay you might get $y(t) = x(t) \cos(2\pi f_c(t - \tau))$. We saw examples of modulated signals before. The signals $x(t)$ and $-x(t)$ form the *envelope* of the modulated signal.



AM radio transmission and channel




This is an AM transmitter – a signal is modulated onto a cosine and sent over the air. The *communication channel* between the transmitter and receiver is noisy, so the received signal is

$$y(t) = A_c m(t) \cos(2\pi f_c t) + \alpha w(t), \quad (10)$$

where f_c is called the *carrier frequency*, A_c is called the *carrier gain* and α^2 is the *noise power*. We assume here that $w(t)$ is *additive Gaussian noise* (white noise).

Feedback



Feedback is a very important part of systems. How do we write the relationship between $y[n]$ and $x[n]$?

$$\underline{y[n]} = \alpha x[n] + \underline{\alpha} y[n-1] \quad (11)$$

$$= \alpha x[n] + \underline{\alpha^2} x[n-1] + \underline{\alpha^2} y[n-2] \quad (12)$$

$$= \alpha x[n] + \alpha^2 x[n-1] + \underline{\alpha^3} x[n-2] + \underline{\alpha^3} y[n-3] \quad (13)$$

$$= \sum_{k=0}^{\infty} \underline{\alpha^{k+1}} x[n-k] \quad (14)$$



Try it yourself

Problem

Try drawing the block diagrams that generate the following signals:

$$y_1(t) = 4x(t) - x(t - 3) + x(t - 5) \quad (15)$$

$$y_2[n] = x[2n - 1] + x[2n] \quad (16)$$

$$y_3(t) = 3x(t - 2) \cos(440\pi t) - 4x(t)^3 \cos(220\pi t) \quad (17)$$

$$y_4[n] = \sum_{k=0}^{\infty} \left(\frac{1}{3}\right)^k x[n - k] \quad (18)$$

~~Try playing $y_3(t)$ with $x(t) = \cos(880\pi t)$ in MATLAB. What do you hear?~~

