

Linear Systems and Signals

Introduction to Laplace Transforms

Anand D. Sarwate

Department of Electrical and Computer Engineering
Rutgers, The State University of New Jersey

2020




Learning objectives

The learning objective for this section is:

- apply the definition of the Laplace transform



The eigenfunction property



Remember the eigenfunction property of LTI systems:

$$\underline{h(t)} * \underline{e^{j\omega_0 t}} = \underline{H(j\omega_0)} \underline{e^{j\omega_0 t}}.$$

complex coefficient (1)

If you put in a complex exponential into a CT LTI system you will get the same complex exponential out, but with a complex scaling $H(j\omega_0)$.

What happens if we we replace $j\omega_0$ with an arbitrary complex number s ?



The Laplace Transform

$$\underline{h(t) * e^{st}} = \int_{-\infty}^{\infty} h(\tau) e^{s(t-\tau)} d\tau = e^{st} \int_{-\infty}^{\infty} h(\tau) e^{-s\tau} d\tau \quad (2)$$

Definition

The (bilateral) Laplace transform of a signal $h(t)$ is defined as

$$H(s) = \int_{-\infty}^{\infty} h(\tau) e^{-s\tau} d\tau. \quad (3)$$

for all values of s where the integral converges.

We will use capital letters for transforms and write $x(t) \xleftrightarrow{\mathcal{L}} \underline{X(s)}$, etc.



Why bilateral?

$$H(s) = \int_{-\infty}^{\infty} h(t) e^{-st} dt.$$

(4)

Handwritten notes above the equation:

$$\int_{-\infty}^{\infty} h(t) u(t) e^{-st} dt = \int_0^{\infty} h(t) e^{-st} dt$$

unilateral

- We call it *bilateral* because t goes from $-\infty$ to ∞ . The so-called *unilateral* transform goes from 0 to ∞ .
- If we only consider *causal* systems, then we can think of $\underline{h(t)}$ as $\tilde{h}(t)u(t)$ since the impulse response has to be 0 for $t < 0$.
- The *unilateral* transform is useful if we are talking about causal systems only.

Convergence and regions thereof

In the definition we said “for all values of s where the integral converges.” What do we mean by that? Take $h(t) = e^{-2t}u(t)$:

$$H(s) = \int_{-\infty}^{\infty} e^{-2t} u(t) e^{-st} dt \quad (5)$$


$$= \int_0^{\infty} e^{-(2+s)t} dt \quad (6)$$

$$= \frac{1}{2+s} \quad (7)$$

if this is negative, integral diverges!

The last line only works as long as $2 + s > 0$ or $s > -2$. What we actually need is $\Re\{s\} > -2$. The set $\{s : \Re\{s\} > -2\}$ is called the region of convergence (ROC) of the transform.

The s -plane



We can think of the Laplace transform as a complex valued function $H : \mathbb{C} \rightarrow \mathbb{C}$. The domain of H is called the s -plane. For $H(s) = \frac{1}{s+2}$ we see that there is a pole at $s = -2$ marked with an \times .

Another example

We can use the sifting property of the Dirac δ function. The identity system has impulse response of $\delta(t)$:

$$\delta(t) \xleftrightarrow{\mathcal{L}} \int_{-\infty}^{\infty} \underbrace{\delta(t)}_{h(t)} e^{-st} dt = \underline{1}. \quad (8)$$

$H(s) = \int_{-\infty}^{\infty} h(t) e^{-st} dt$

$\delta(t) \xleftrightarrow{\mathcal{L}} 1$
 $\text{ROC} = \mathbb{C}$

What about a system that delays its input by τ ?

$$\delta(t - \tau) \xleftrightarrow{\mathcal{L}} \int_{-\infty}^{\infty} \delta(t - \tau) e^{-st} dt = \boxed{e^{-s\tau}}. \quad (9)$$

$\delta(t - \tau) \xleftrightarrow{\mathcal{L}} e^{-s\tau}$
delay by τ

We will see other examples in the next sections.



Coming up next

In the next few presentations we will dig a little deeper:

- examples of calculating the Laplace transform
- describing the ROC and its properties
- showing how convolution and Laplace transforms are related

$$\begin{array}{c} h(t) * x(t) \\ \downarrow \mathcal{L} \\ H(s) X(s) \end{array}$$

A critical fact to remember is that a Laplace transform of a signal is not just the formula – you need to describe the region of convergence (ROC) as well.

